

G-MOUNT HF (M5)

Mobile low-profile antenna mount for roof mounting

Mobile mount for roof mounting of antenna whips supplied with external M5 threaded stud. It can be mounted from the inside or from the outside.

- LOW PROFILE DESIGN
- TILTABLE IN ALL DIRECTIONS



ELECTRICAL SPECIFICATIONS

Frequency	0 - 2500 MHz (External antenna whips)
Impedance	50 ohm

MECHANICAL SPECIFICATIONS

Color	Black
Height above root	30 mm
Diameter	Ø 33 mm
Mounting	Bolt-on (From inside or outside - Maximum torque on nut 4.5 Nm)
Mounting Place	On vehicle roof
Mounting Instruction	The antenna whip (not supplied) is tiltable 15° in all directions by bending the topsection of the base. NOTE! Bending one time only !
Height above roof	30 mm
Mounting hole	Mounting from inside: Ø 13 mm, Mounting from outside: Ø 19 mm
Build-in Depth	Approx. 12 mm
Materials	ABS, POM, PE, brass and steel
Operating Temperature	-40C to +70C
Connector	See "ORDERING INFO" (Other types available)
Cable	See "ORDERING INFO" (Other lengths available)
Ingress protection	IP65 (When mounted)

ORDERING INFORMATION

P/N	G16060 (0.15 m cable + FME-male)
P/N	G16060IP (0.15 m cable + FME-male - Bulk packing)
P/N	G16062 (0.15 m cable + SMA-female)
P/N	G16062IP (0.15 m cable + SMA-female - Bulk packing)
P/N	G16064IP (5 m cable + SMA-male - Bulk packing)
P/N	G16065IP (5 m cable + open end - Bulk packing)

PACKAGING INFORMATION

Type	Bulk packing or individually packing in Polybag (See "Part No.")
------	--

MOUNTING INSTRUCTION

